

BITUMEN PRIMERS

BITAREL® BITUMEN PRIMER

TS BY 690590146.017-2016

Description: BITAREL® bitumen primer is a solution of petroleum bitumen, organic solvents and processing additions.

Purpose: used to prepare (priming) the base of isolated surfaces (concrete, wooden and metal) for better adhesion of alignable roofing and waterproofing materials, shingle, for better adhesion of bitumen materials, before applying road sealants and tapes.

Recommendations before usage: before using, the bitumen primer needs to be stirred until a homogenous mix. Add solvent if necessary. Apply the primer with a brush, capron brush or a paint roller. If environment temperature drops below 0°C, the bitumen primer should be kept in a warm room for 24 hours. The working surface must be dry and clear from dirt, dust, sand or trash. Working temperature range is -20 °C to +40°C.

Average consumption: 0.16-0.35 kg/m² (primer consumption depends on base texture)

Storage: should be kept in packaging and conditions with no direct sunlight at -20°C to +30°C

Guaranteed shelf life: 18 months.

Packaging: 5, 10, 20 or 50l sealed metal containers.

BITAREL bitumen primer complies with GOST R, DSTU B.V.2.7-108-2001.



ADVANTAGES

- Multi-purpose: applicable to any surface – metal, wooden, concrete
- High adhesiveness to any surface
- Good penetration ability
- Short drying period
- Small consumption

Basic physical and mechanical characteristics:

No	Item	Standard for the type
		Bitumen primer
1	Non-volatile matter content, %, at least	30
2	Viscosity, s, at least	10
3	Drying period of the applied layer at 20°C, h, not exceeding	12